


#### **TECHNICAL DRAWING**



**PHOTO** 



PRODUCT FAMILY: SHOWER COLUMN - ELEGANCE SERIES CODE: ELSHDMSXN
DESCRIPTION: Safety shower column with hand shower: left shelf. Black finishes.

#### **MECHANICAL PERFORMANCES:**

Load capacity at vertical traction 200 kg. Maximum flow rate: 3 bar: 10 l/min Connection to water plug high or low.

#### APPROVALS/CERTIFICATIONS:

### **PRODUCT FEATURES:**

Safety shower column mat black finish with: hand shower in ABS mat black (3 jets), flexible mat black and shelf in painted aluminium left position. The product is made of a column diameter 32 mm made of painted stainless steel AISI304, able to resists to a traction resistance of 200 kg. Inside the columnthere is a system of tubes and connections in order to conduct the water to thehand shower, in order to allow the use of water inlet 1 / 2 " G pre-existinginto the wall. Taps not included in the product. It isnecessary to have amixer able to adjust the temperature and water supply.

#### FIXING/INSTALLATION:

Column wall mounted with n° 2/3 fasteners

Fixation of the shelf with 2 fasteners

Connect inlet connection to the wall water intake. Fasteners and screws not included in the package.

Choose a proper fastener, considering the type of wall onwhich you are going to

install the column.

Dimension of holes for fixing screws on the wall: Ø 10,5 mm

Connection for water intake 1/2"

#### PRODUCT COMPOSITION: MATERIALS:

N° 1Shower column made of stainless steel aisi 304 - Aluminium - Brass - painted  $\ensuremath{N^\circ}$  1Hand shower made of white ABD  $\ensuremath{N^\circ}$  1 Flexible and compenents like tubesand connections

Check periodically the correct fixation of the accessories. Make a proper cleaning with water and soap, do not use abrasive or corrosive products. Do not use for purposes that are different from inteded purposes.Clean regularly the thermostatic cartridge

# TREATEMENTS:

TOLERANCES:

## PACKAGING OF THE PRODUCT:

Single package with pluriball in single carton 1500 x 110 x 120 mm. Weight: 2,5 kg

The above mentioned information cannot be considered as binding. Thermomat Saniline Srl

reserves the right to make technical and aesthetic changes without any prior notice.



