



PHOTO



PRODUCT FAMILY: THERMOSTATIC MIXERS - THERMOMIX SERIES

CODE: RUMT201CFI

DESCRIPTION: Exposed thermostatic shower mixer with 1/2" lower water outlet.

HYDRAULIC PERFORMANCES:

Flow rate: over 24 l/min at 3 bar.

APPROVALS/CERTIFICATIONS:

TUV system certification UNI EN ISO 9001:2008.

ACS and WRAS certified thermostatic cartridge.

PRODUCT FEATURES:

Cast brass body with replaceable thermostatic cartridge and temperature stop button set at 38°C. Check valves included. 1/2" lower outlet for flexible hose installation.

Inlets: 3/4" G F with 3/4" GF- 1/2" GM eccentric and chrome-plated escutcheon plate; centre distance according to UNI EN 1111 regulation to fit both old and new systems. Levers made of chrome-plated ABS.

The body's temperature is never higher than the mixed water one, in order to avoid scalds.

FIXING/INSTALLATION:

3/4" G F or 1/2" G F inlets with eccentric.

Distance of the body from the wall: approx. 35 mm.

Carefully the instruction sheet for a correct installation.

MAINTENANCE:

Check the correct fastening of the mixer periodically.

Clean the exposed body with water and soap or other suitable cleaning products;

avoid using chemical, aggressive or abrasive agents. Dry with a soft cloth.

In case of extraordinary maintenance (cartridge cleaning), check the instruction sheet.

PRODUCT COMPOSITION:

N° 1 Exposed body - Cast brass (Alloy CB75636) - Polished, chrome-plated

N° - O-ring - NBR

N° - Cartridge components - Brass UNI EN 12164 CW14

N° 2 Handles - ABS - Brass/Zamak - chrome-plated

N° 2 Check valves

N° - Springs - Stainless steel AISI 302

N° 1 Thermal wax element

TOLERANCES:

PACKAGING OF THE PRODUCT:

Packed in cardboard box 80 x 85 x 290 mm.

Weight: 2 kg

The above mentioned information cannot be considered as binding. Thermomat Saniline S.r.l. reserves the right to make technical and aesthetic changes without any prior notice.

ST_PRODOTTO: RUMT201CFI	APPROVATO
REV.01 DEL 06/10/2023	R.T.