


TECHNICAL DRAWING



Art.	Vaso	A	B	C	D	E	Apertura frontale	Coperchio
430-E	420-ES	450	375	300	245	160 (con eccentrico)	SI	SI

Misure in mm.

PHOTO



PRODUCT FAMILY: SANITARYWARE

CODE: 430

DESCRIPTION: Toilet seat with lid for toilet code 420, 420-B, 460, 460-B.

APPROVALS/CERTIFICATIONS:

TUV system certification UNI EN ISO 9001:2008.

PRODUCT FEATURES:

Toilet seat with lid for toilet code 420, 420-B, 460, 460-B.

These seats and lid are urea printed, a crystalline polymer belonging to the family of polyesters. Solvent resistant, it features excellent mechanical properties, it is very light, fireproof and it does not turn yellow.

A peculiar enveloping lid protects the seat from dust. Complete with stainless steel hinges. A plastic key is included, to easily tighten or release the screws. Through bolt fixing.

NB: EACH SEAT FITS A SPECIFIC MODEL OF TOILETS. IF MOUNTED ON OTHER TOILETS, IT COULD NOT ADAPT PERFECTLY, THUS

CAUSING THE HINGES TO BREAK. IT IS HIGHLY RECOMMENDED THAT YOU USE THE SEAT CORRESPONDING TO EACH TOILET. STANDARD SEATS ARE USED FOR TOILETS WITH MORE COMMON SHAPES. NEVERTHELESS, WE RECOMMEND CHECKING THE SHAPE AND DIMENSIONS BEFORE THE INSTALLATION.

FIXING/INSTALLATION:

Fasten the seat to the toilet using the included screws, making sure that the fasteners are securely tightened.

The front bumpers must lean against the toilet edge, the back ones must be 3-4 mm raised.

MAINTENANCE:

Check the correct fastening of the seat periodically. Avoid backlashes to the fasteners and incorrect movements, which could damage the hinges. Clean with water and soap or other suitable products, do not use abrasive or corrosive agents. Dry with a soft cloth.

PRODUCT COMPOSITION:

- N° 1 Seat with lid - Urea
- N° 2 Hinges - Inox stainless steel
- N° 4 Bumpers - Linear polyethylene
- N° 4 Lid bumpers - Linear polyethylene

PACKAGING OF THE PRODUCT:

PRODUCT PACKAGING:
Packed in cardboard box 380 x 555 x 55 mm.
Multiple packing (5 pcs) in individual cardboard boxes + 580 x 330 x 400 mm box.
Weight: 3,8 kg

The above mentioned information cannot be considered as binding. Thermomat Saniline Srl reserves the right to make technical and aesthetic changes without any prior notice.

ST_PRODOTTO: 430 - 1	APPROVATO R.T.
REV.01 DEL 19/09/11	

THERMOMAT SANILINE SRL
Via M. Curie, 7 - 46034 Borgo Virgilio (Mantova) ITALY
Tel. + 39 0376 4473
www.thermomat.com - e-mail: info@thermomat.com

