


PRODUCT TECHNICAL SHEET

TECHNICAL DRAWING



PHOTO



PRODUCT FAMILY: HANDBARS AND HANDRAILS – PAINTED SERIES
CODE: 300-I
DESCRIPTION: Vertical wall-to-wall grab bar. Electrical insulation. White colour.

MECHANICAL PERFORMANCES:
 Maximum load 150 kg.

APPROVALS/CERTIFICATIONS:
 TUV system certification UNI EN ISO 9001:2008.
 Declaration of Conformity according to European Medical Device Directive 93/42.
 Reference regulations: Pr EN 1874; UNI EN 12182; UNI CEI EN ISO 14971; UNI EN 1041.

PRODUCT FEATURES:

Ø 32 cold bent body, complete with center spacer, mounting flanges and flange covers.
 The mounting flanges electrically insulate the product.

FIXING/INSTALLATION:

Wall mounting by n° 9 plugs.
 Plugs are not included in the package.
 Read the instruction sheet to choose the suitable plugs according to the type of wall.

PRODUCT COMPOSITION:

N° 2 Pipes Ø32 x 15/10 - Fe Po4 - Zinc-coated and painted RAL9016
 N° 3 Mounting flanges Nylon PA6 RAL9016
 N° 3 FLange covers Nylon PA6 RAL9016
 N° 3 Flange fixing screws Steel Tropicalized
 N° 2 Fixing bushings Brass UNI EN 12164 CW614N
 N° 1 Support Nylon PA6 RAL9016

MAINTENANCE:

Check the correct fastening of the accessories periodically.
 Perform a proper cleaning with water and soap, do not use abrasive or corrosive agents or coarse sponges.

TOLERANCES:

GENERAL TOLERANCES - LENGTH (mm)
 0÷300 ±3 301÷600 ±4 601÷2000 ±5

PACKAGING OF THE PRODUCT:

Individually wrapped in bubble wrap and packed in cardboard box 230 x 40 x 1840 mm.
 Weight: 2,5 kg

ST_PRODOTTO: 300-I	APPROVATO - 1 R.T.
REV.01 DEL 26/02/14	

