

TECHNICAL DRAWING
Lunghezza doccetta : 130 mm

Diametro : 40 mm

Lunghezza flessibile : 1200 mm, con connessioni a girello da ½" e da ½" conico

Supporto a muro:

Lunghezza: 50 mm

Diametro: 35 mm

Tenuta statica: 0 / 15 bar

Tenuta colpo d'ariete: 25 bar

Caratteristiche tecniche flessibile PVC e retinato nylon:

Ø 9 x 13,8 nominale, triplo strato, trasparente o colorato.

Pressione di esercizio: 0 / 5 bar

Pressione di scoppio: 15 bar

Temperatura di esercizio: -20°C / +60°C

Tenuta: 40 bar acqua fredda; 25 bar acqua calda

PHOTO



PRODUCT FAMILY: ACCESSORIES

CODE: 520

DESCRIPTION: Bidet shower head.

CERTIFICATIONS:

TUV system certification UNI EN ISO 9001:2008.

PRODUCT FEATURES:

Bidet shower head, with lever control, with holder and flexible hose, featuring a chrome-plated ABS body, an ergonomic handle, a back-positioned lever and a decorative grey ABS ring.

Suitable for personal cleansing. The flexible hose is 1200 mm long and is made of three-layer PVC and reinforced nylon with transparent polished

finish, complete with ½" swivel joint and ½" conical nut with swivel joint (length: 30 mm); connecting gaskets included.

Wall holder made of chrome-plated ABS included, complete with wall mounting screws and plugs.

FIXING (INSTALLATION):

Mount the holder on the wall by means of the included screws and plugs.

Connect the flexible hose to the shower head and to the power supply, using the

relevant gaskets.

Position the shower head on the holder.

MAINTENANCE:

Check the correct fastening of the product periodically.

Clean with water and soap or other suitable cleaning products. Do not use products

containing chlorine, hydrochloric acid, or any of their derivatives, or other acids or

bases, even if diluted.

Dry with a soft cloth.

PRODUCT COMPOSITION:

N° 1 Shower head with lever - ABS - Chrome-plated

N° 1 Flexible hose 1200 mm - PVC, reinforced nylon

N° 2 Gaskets NBR

N° 1 Holder - ABS - Chrome-plated

N° 2 Screws + plugs

PRODUCT PACKAGING:

Packed in polybag and in cardboard box 190 x 190 x 50 mm.

Weight: 0,3 kg