


TECHNICAL DRAWING

Ingombro massimo: 120 x 120 mm
 H parte incassata: circa 60 x Ø60 mm
 H parte superficiale: 35 mm
 In dotazione tubo corrugato nero da incasso e tubo pneumatico trasparente 2,5 m.

<p>PHOTO</p> <div style="text-align: center; margin-top: 20px;">  </div>	<p>PRODUCT FAMILY: ACCESSORIES CODE: 553 DESCRIPTION: Pneumatic foot operated flush button, floor mounted.</p> <hr/> <p>CERTIFICATIONS: TUV system certification UNI EN ISO 9001:2008.</p>
<p>PRODUCT FEATURES: Pneumatic foot operated flush button, for installation in floor. Complete with stainless steel covering plate, concealed protection pipe, fastening material, expanded polystyrene drill template. Rubber push button, screws and plugs for floor fastening included. It suits all types of cisterns. 2,5 pneumatic hose included</p>	
<p>FIXING (INSTALLATION): Introduce the pneumatic hose in the protection pipe and connect it to the push button. Fasten the button to the floor by means of the screws and plugs included.</p>	<p>MAINTENANCE: Check the correct fastening of the accessories periodically. Perform a proper cleaning with water and soap, do not use abrasive or corrosive agents.</p>
<p>PRODUCT COMPOSITION: N° 1 Protection pipe - Plastic N° 1 Covering plate - Stainless steel N° 1 Drill template - Expanded polystyrene N° 1 Set of screws N° 1 Pneumatic hose</p>	<p>PRODUCT PACKAGING: Packed in polybag and cardboard box 260 x 260x 120 mm. Weight: 0,7 kg</p>

The above mentioned information cannot be considered as binding.

Thermomat reserves the right to make technical and aesthetic changes without any prior notice.

ST_PRODOTTO: 553	APPROVATO - 1
REV.01 DEL 17/05/12	R.T.

